

FDV – DOKUMENTASJON		Nr.:111
		Rev.:
		Dato: 19.12.2016
Produktspesifikasjon	PERFECT cable gland M/R (reduced sealing)	
Produktnavn	50.6xx M/R	
Anvisning for drift	Ingen anvisning for drift	
Vedlikehold	Ingen vedlikehold	
Henvisninger Vedlegg	Datablad	
Produsent	Jacob GmbH Elektrotechnische Fabrik Gottlieb-Daimler-Strasse 11 D-71394 Kernern Germany	
Importør	EFA Elektro AS, Postboks 593, 1411 Kolbotn, Norway Tlf. 66812400 e-mail: post@efa.no - www.efa.no	

PERFECT cable gland

50.6xx M/R

Dome nut	Brass CuZn39Pb3, nickel-plated
Lamellar insert	Polyamide PA6 V-2
Sealing ring/outer part	Polychloroprene-Nitrile rubber CR/NBR
Sealing ring/inner part	TPE TPS
Gland body	Brass CuZn39Pb3, nickel-plated
O-ring	Nitrile rubber NBR
Connecting thread	metric, as per EN 60423



Properties

	<ul style="list-style-type: none"> reducing sealing ring for small cable diameter integrated anchorage wide sealing and clamping range protection against twisting, easy-to-install
Temperature range (°C)	-20°C / +100°C (dynamic) -40°C (static, short term)
Protection grade	68 5 IP69*
Test standard	EN 50262 UL 514B
VDE licence	40020901
UL / CSA-File	E140310
GL T.A. Certificate	44 608 - 07 HH
Comment	details about tests - see annex

